Carrier®
HEATING & COOLING

50GL-2SB

50GL 024-060 HIGH-EFFICIENCY SINGLE-PACKAGE ELECTRIC COOLING UNITS with optional ELECTRIC HEAT

— PERFORMANCE DATA

— CERTIFIED DIMENSION PRINT

— CERTIFIED ROOF CURB DIMENSION PRINT

Puron®
the environmentally sound refrigerant

© 2001 Carrier Corporation

Form 50GL-2SB Cancels 50GL-1SB Printed in U.S.A. 6-01 Catalog No. 515-00008

Date:	Supersedes:	50GL024-060 Single-Package Electric Cooling Units	50GL	Rev.:
JOB DATA:		LOCATION:		
BUYER:		BUYER P.O. #	CARRIER #	
UNIT NUMBER:		MODEL NUMBER:		
PERFORMANCE DATA CERTIFIED BY:			DATE:	

50GL units are high-efficiency, self-contained, electric cooling units designed for easy installation and maintenance and dependable performance. All units have discharge openings for either horizontal or downflow configuration, and all have low sound levels. Units are intended for outdoor installation and may be located on a rooftop, or a ground-level concrete slab, or directly on the ground if local codes permit. This unit features Puron® refrigerant, which is environmentally sound.

FEATURES

- Puron® refrigerant, the environmentally friendly alternative.
- Energy Star Rated @ 12 SEER.
- Standard five year limited warranty and 10 year on compressor.
- Variable speed blower motor option.
  - • Better dehumidification
  - • Improved SEER
  - • Reduced sound
- Unit is certified and listed by UL and c-UL. Unit is rated in accordance with ARI Standard 210.
- Low sound ratings; as low as 72 dB.
- Units are pre-wired, pre-piped, and pre-charged for minimum installation expense.
- Compressor vibration isolation provides quieter operation.
- Easily converted for downflow operation with included horizontal duct covers.
- Cabinets are constructed of heavy-duty, phosphated, zinc coated pre-painted steel capable of withstanding 500 hours in salt spray.
- Easy-to-service cabinets with single-panel accessibility.
- Liquid refrigerant driers promote clean, unrestricted operation.
- Direct-drive multi-speed, permanent split capacitor (PSC) indoor motor is standard.
- Direct-drive, PSC outdoor fan motor.
- Coils constructed of aluminum fins bonded to copper tubes.
- Louvered grille provides hail and vandalism protection.
- Envirotuff™ rust-proof unit base pan.
- Sloped drain pan minimizes standing water in the unit.
- High and low/loss of charge pressure switches to ensure proper performance and longer compressor life.
- Refrigerant service connections make checking operating pressures easier.
- Copper & pre-coated fin coils are available from the factory by special order, for use in corrosive environments.
- Three-phase units available.

PERFORMANCE DATA

Unit Operating Weight_____lb (unit); _____lb (curb)

COOLING

Net Total Capacity _____ Btuh
Net Sensible Capacity _____ Btuh
Compressor Power Input_____kW @ _____ °F Outdoor-Air Temperature
Indoor Entering-Air db_____°F wb _____ °F
Seasonal Energy Efficiency Ratio _____
CFM _____ Ext. Static Pressure_____in. wg
Indoor Fan Motor _____Hp_____ Rpm_____Bhp
Type:_____ Standard_____ Variable

HEATING

Power Input To Unit_____ kW
Outdoor-Air Temp _____ °F (Winter Design)
Electric Capacity Required _____ Btuh
_____ KW Heater Selected

ELECTRICAL DATA

Unit Power Supply_____Volts_____Phase_____ Hz
Minimum Circuit Amps_____Maximum Overcurrent Protection_____

FACTORY INSTALLED OPTIONS

- ☐ Pre Coated Coils
- ☐ Copper/Copper Coils
- ☐ Electronic Variable-Speed Blower Motor
  —ICM Motors (Integrated Control and Motor) provide variable-speed operation to optimize comfort levels year round. They are also more economical to operate than standard motors.

FIELD-INSTALLED ACCESSORIES

- ☐ Economizer
- ☐ Manual Air Damper
- ☐ Filter Rack
- ☐ Flat Roof Curb:
  - ☐ 8 in. Height
  - ☐ 14 in. Height
- ☐ Thermostat
  - ☐ Programmable
  - ☐ Non-Programmable
- ☐ Crankcase Heater
- ☐ Time Guard® II Device
- ☐ Compressor Hard Start Kit
- ☐ 0°F Low Ambient Kit
- ☐ Square-to-Round Duct Transition Kit
- ☐ Electric Heat Package-5-20KW

NOTES: _____

CERTIFIED DIMENSION PRINT

UNITED TECHNOLOGIES CARRIER
P O BOX 4808 SYRACUSE N. Y. 13221
THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER CORPORATION'S WRITTEN CONSENT.
SUBMISSION OF THESE DRAWINGS OR DOCUMENTS DOES NOT CONSTITUTE PART PERFORMANCE OR ACCEPTANCE OF CONTRACT

UNIT	ELECTRICAL CHARACTERISTICS	UNIT WT. LBS.	UNIT WT. KG.	UNIT HEIGHT "A"	CENTER OF GRAVITY MM/IN X	Y	Z
50GL024	208-230-1-60	270	122.5	940.3[37.02]	469.9[18.5]	368.3[14.5]	406.4[16.0]
50GL030	208/230-1-60, 208/230-3-60	291	132.0	991.1[39.02]	495.3[19.5]	393.7[15.5]	447.0[17.6]
50GL036	208/230-1-60, 208/230-3-60, 460-3-60	299	135.6	889.5[35.02]	495.3[19.5]	387.4[15.3]	419.1[16.5]

REQUIRED CLEARANCES TO COMBUSTIBLE MATL.

	MILLIMETERS [IN]
TOP OF UNIT	355.6 [14.00]
DUCT SIDE OF UNIT	50.8 [2.00]
SIDE OPPOSITE DUCTS	355.6 [14.00]
BOTTOM OF UNIT	12.7 [0.50]
ELECTRIC HEAT PANEL	914.4 [36.00]

NEC. REQUIRED CLEARANCES.

	MILLIMETERS [IN]
BETWEEN UNITS, POWER ENTRY SIDE	1066.8 [42.00]
UNIT AND UNGROUNDED SURFACES, POWER ENTRY SIDE	914.0 [36.00]
UNIT AND BLOCK OR CONCRETE WALLS AND OTHER GROUNDED SURFACES, POWER ENTRY SIDE	1066.8 [42.00]

REQUIRED CLEARANCE FOR OPERATION AND SERVICING

	MILLIMETERS [IN]
EVAP. COIL ACCESS SIDE	914.0 [36.00]
POWER ENTRY SIDE	914.0 [36.00]
(EXCEPT FOR NEC REQUIREMENTS)	
UNIT TOP	914.0 [36.00]
SIDE OPPOSITE DUCTS	914.0 [36.00]
DUCT PANEL	304.8 [12.00]*

*MINIMUM DISTANCES: IF UNIT IS PLACED LESS THAN 304.8 [12.00] FROM WALL SYSTEM, THEN SYSTEM PERFORMANCE MAYBE COMPROMISED.

DIMENSIONS IN [] ARE IN INCHES



TOP VIEW



LEFT SIDE VIEW



FRONT VIEW



RIGHT SIDE VIEW



REAR VIEW

05/11/00 . SINGLE ZONE ELECTRIC COOLING 50GL024-036 50GL500028 .

C01005

Cut along dotted line

Cut along dotted line

CERTIFIED DIMENSION PRINT

UNITED TECHNOLOGIES CARRIER — P O BOX 4808 SYRACUSE N. Y. 13221

THIS DOCUMENT IS THE PROPERTY OF CARRIER CORPORATION AND IS DELIVERED UPON THE EXPRESS CONDITION THAT THE CONTENTS WILL NOT BE DISCLOSED OR USED WITHOUT CARRIER CORPORATION'S WRITTEN CONSENT.

SUBMISSION OF THESE DRAWINGS OR DOCUMENTS DOES NOT CONSTITUTE PART PERFORMANCE OR ACCEPTANCE OF CONTRACT

UNIT	ELECTRICAL CHARACTERISTICS	UNIT WT. LBS.	UNIT WT. KG.	UNIT HEIGHT "A"	CENTER OF GRAVITY MM/IN X	Y	Z
50GL042	208-230-1-60, 208/230-3-60, 460-3-60	321	145.6	990.2[38.98]	520.7[20.5]	425.5[16.8]	421.6[16.6]
50GL048	208-230-1-60, 208/230-3-60, 460-3-60	326	147.8	990.2[38.98]	495.3[19.5]	447.6[17.6]	457.2[18.0]
50GL060	208-230-1-60, 208/230-3-60, 460-3-60	399	181.0	1091.7[42.98]	520.7[20.5]	412.8[16.3]	447.0[17.6]



TOP VIEW

REQUIRED CLEARANCES TO COMBUSTIBLE MATL.

	MILLIMETERS [IN]
TOP OF UNIT	355.6 [14.00]
DUCT SIDE OF UNIT	50.8 [2.00]
SIDE OPPOSITE DUCTS	355.6 [14.00]
BOTTOM OF UNIT	12.7 [0.50]
ELECTRIC HEAT PANEL	914.4 [36.00]

NEC. REQUIRED CLEARANCES.

	MILLIMETERS [IN]
BETWEEN UNITS, POWER ENTRY SIDE	1066.8 [42.00]
UNIT AND UNGROUNDED SURFACES, POWER ENTRY SIDE	914.0 [36.00]
UNIT AND BLOCK OR CONCRETE WALLS AND OTHER GROUNDED SURFACES, POWER ENTRY SIDE	1066.8 [42.00]

REQUIRED CLEARANCE FOR OPERATION AND SERVICING

	MILLIMETERS [IN]
EVAP. COIL ACCESS SIDE	914.0 [36.00]
POWER ENTRY SIDE	914.0 [36.00]
(EXCEPT FOR NEC REQUIREMENTS)	
UNIT TOP	914.0 [36.00]
SIDE OPPOSITE DUCTS	914.0 [36.00]
DUCT PANEL	304.8 [12.00]*

*MINIMUM DISTANCES: IF UNIT IS PLACED LESS THAN 304.8 [12.00] FROM WALL SYSTEM, THEN SYSTEM PERFORMANCE MAYBE COMPROMISED.

DIMENSIONS IN [] ARE IN INCHES



LEFT SIDE VIEW

FRONT VIEW



RIGHT SIDE VIEW



REAR VIEW

DATE 05/11/00 — SUPERSEDES . — SINGLE ZONE ELECTRIC COOLING 50GL042-060 — 50GL500030 .

C01006

CERTIFIED DIMENSION PRINT

SUBMITTAL

Roof Curb for Small Cabinet

SUBMITTED TO _____
COMPANY: _____
DRAWN BY: A.L.L.
JOB NAME: _____
EQUIPMENT: _____
NOTES: _____

ODS Catalog Ordering No.	A
CPCRFCURB006A00	8"
CPCRFCURB007A00	14"

Feature:
- Constructed of heavy gage galvanized steel.
- Roofcurb ships knocked down in corrugated box.
- Quick-clip design for easy field assembly.
- Insulated deck pan.
- Gasketing package and hardware included.
- Wood nailer provided.







* Duct size

SIDE VIEW

C00077

Cut along dotted line

Cut along dotted line

CERTIFIED DIMENSION PRINT

SUBMITTAL

Roof Curb for Large Cabinet

SUBMITTED TO: _____
COMPANY: _____
DRAWN BY: M. HARGIS
JOB NAME: _____
EQUIPMENT: _____
NOTES: _____

FEATURES:

- Constructed of heavy gage galyanized steel.
- Quick-clip design for easy field assembly.
- Ships knocked down w/corrugated box.
- Gasket package for complete outer perimeter flange and around duct openings.
- Wood nailer provided.



Side View



ODS Catalog Ordering No.	A
CPRFCURB008A00	8"
CPRFCURB009A00	14"

C00078

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.